



## AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (Currently Amended) A power splitter device comprising:  
a power input port;  
at least three power output ports each having a separate, resettable overcurrent protection circuit, each of said overcurrent protection ~~circuit~~ circuits having its own maximum current rating; and

a port switch configured to provide power from said input port to selectable combinations of one or more said output ports, including at least one combination of two or more said output ports, said port switch restricted from selecting ~~and further configured to prevent power from being applied to~~ all said output ports simultaneously.

2. (currently amended) A device in accordance with Claim 1 wherein said port switch is further configured to ~~prevent power from being applied to~~ restrict selection of any combination of said output ports having overcurrent protection circuits with maximum current ratings totaling more than a preselected maximum current.

3. (currently amended) A device in accordance with Claim 2, wherein ~~said a~~ highest of said maximum current ~~rating~~ ratings of said overcurrent protection circuits is equal to said preselected maximum current.

RECEIVED  
MAY 20 2003  
TECHNOLOGY CENTER 2800

4. (currently amended) A device in accordance with Claim 2, wherein:  
one of said overcurrent protection ~~circuit~~ circuits is a high current circuit  
having a highest maximum current rating; and  
said port switch is configured to provide current to said output port having the  
high current circuit only in combination with no other said output port.

5. (original) A device in accordance with Claim 1 wherein said ports are  
selected from the group consisting of 12 VDC power connectors and ARINC 628  
connection points.

6. (original) A device in accordance with Claim 1 wherein said resettable  
overcurrent protection circuits are user-replaceable.

7. (currently amended) A power distribution system comprising:  
a power source configured to provide power to a plurality of seat connectors;  
a branch level overprotection circuit having a maximum current rating and  
providing overcurrent protection for current drawn in a branch of said system  
comprising a plurality of seat connectors; and  
a power splitter device having a power input port configured to receive power  
from one of said seat connectors, at least three power output ports each having a  
separate, resettable port level overcurrent protection circuit, each of said overcurrent  
protection ~~circuit~~ circuits having its own maximum current rating; and a port switch  
configured to provide power from said input port to selectable combinations of one or  
more said output ports, including at least one combination of at least two said output

ports, said port switch further configured to restrict selection of ~~to prevent power from being applied to~~ all said output ports simultaneously.

8. (currently amended) A system in accordance with Claim 7 wherein said port switch is further configured to ~~prevent power from being applied to~~ restrict selection of any combination of said output ports having port level overcurrent protection circuit with maximum current ratings totaling more than a prorated seat connector share of said maximum current rating of one of said branch level overcurrent protection circuits.

9. (currently amended) A system in accordance with Claim 8, wherein said a highest of said maximum current rating ratings of said overcurrent protection circuits is equal to said prorated seat connector share.

10. (currently amended) A system in accordance with Claim 9, wherein:  
one of said port level overcurrent protection ~~circuit~~ circuits is a high current circuit having a highest maximum current rating; and

said port switch is configured to provide current to said output port having the high current circuit only in combination with no other said output port.

11. (original) A system in accordance with Claim 7 wherein said input port and said output ports are selected from the group consisting of 12 VDC power connectors and ARINC 628 connection points.

12. (original) A system in accordance with Claim 7 installed on a mobile platform.

13. (original) A system in accordance with Claim 12 wherein the mobile platform is an airplane.

14. (currently amended) A method for supplying power to a plurality of passenger devices at a passenger seat of a mobile platform, said method comprising:

*Al conf*

~~selecting a combination of one or more~~ providing at least three output ports coupled a port switch configured to selectively power said output ports including at least one combination of two or more output ports from a ~~to be powered by the seat connector, utilizing a port switch,~~ wherein each output port has a separate overcurrent protection circuit having a maximum current rating; ~~and wherein combinations selectable by the port switch include at least one combination of two or more output ports;~~ out of at least three output ports; and

restricting the port switch from selecting combinations of output ports having overcurrent protection circuits with maximum ratings having a total greater than a preselected maximum current.

15. (original) A method in accordance with Claim 14 wherein the preselected maximum current is a prorated seat connector share, and further comprising the step of determining a prorated seat connector share.

16. (original) A method in accordance with Claim 14 wherein the mobile platform is an airplane.

17. (original) A method in accordance with Claim 14 further comprises replacing at least one of the overcurrent protection circuits with another having a different maximum current rating.

---

18. (represented - formerly dependent Claim 4) A power splitter device comprising:

a power input port;

at least three power output ports each having a separate, resettable overcurrent protection circuit, each of said overcurrent protection circuits having its own maximum current rating and wherein one of said overcurrent protection circuit is a high current circuit having a highest maximum current rating; and

a port switch configured to provide power from said input port to selectable combinations of one or more said output ports, including at least one combination of two or more said output ports, and further configured to prevent power from being applied to all said output ports simultaneously, to prevent power from being applied to any combination of said output ports having overcurrent protection circuits with maximum current ratings totaling more than a preselected maximum current, and to provide current to said output port having the high current circuit only in combination with no other output port.

19. (represented - formerly dependent Claim 10) A power distribution system comprising:

a power source configured to provide power to a plurality of seat connectors;  
a branch level overprotection circuit having a maximum current rating and providing overcurrent protection for current drawn in a branch of said system comprising a plurality of seat connectors; and

*add  
circuit*  
a power splitter device having a power input port configured to receive power from one of said seat connectors, at least three power output ports each having a separate, resettable port level overcurrent protection circuit, each of said port level overcurrent protection circuits having its own maximum current rating, wherein a highest of said maximum current ratings of said port level overcurrent protection circuits is equal to said a prorated seat connector share and is a high current circuit having a highest maximum current rating;

and a port switch configured to provide power from said input port to selectable combinations of one or more said output ports, including at least one combination of at least two said output ports, said port switch further configured to prevent power from being applied to all said output ports simultaneously, to prevent power from being applied to any combination of said output ports having port level overcurrent protection circuit with maximum current ratings totaling more than said prorated seat connector share of said maximum current rating of one of said branch level overcurrent protection circuits, and wherein said port switch is configured to provide current to said output port having the high current circuit only in combination with no other said output port.

---